

- **WATER FOR COMPACTION** Added a new note to pay for water for compaction of granular materials for quantities over 100Mgal or for quantities less than 100Mgal if paid as a bid item. This note will be used when rates are not provided.
- **FULL DEPTH RECLAMATION, SHOULDER** Added the following note and table.

The asphalt mix and granular base material will meet the following gradation:

Sieve Size	Percent Passing
2 inch	100
1 inch	95-100

- **FULL DEPTH RECLAMATION (FDR)** Added the following note and table.

The asphalt mix and granular base material will meet the following gradation:

Sieve Size	Percent Passing
2 inch	100
1 inch	95-100

- **ASPHALT CONCRETE COMPOSITE** Added an optional note for use when MSCR binders are specified. Added a rate for blotting sand for prime.
- Added the following to the end of the 2nd paragraph, “The final shaping of the granular material on the shoulder must be completed after the Cold Milling Asphalt Concrete operation.”
- **CLASS Q R HOT MIXED ASPHALT CONCRETE** Non-Alternate Bid Item note. In the first instruction “will” was corrected to say “will not”.
- **COLD MILLING or MICRO-MILLING ASPHALT CONCRETE** Added a paragraph that limits the time from when cold milling is complete and when the asphalt paving must be completed.
- **CONTINUOUSLY REINFORCED PCC PAVEMENT REPAIR** Changed the opening strength required from 3,500 psi to 2,500 psi.
- **NONREINFORCED PCC PAVEMENT REPAIR** Changed the opening strength required from 3,500 psi to 2,500 psi.
- **REPAIR TYPE A SPALLS** Added the following note. “Traffic will not be permitted over the area until the repair material has reached 2,000 psi.”
- **PROTECTION OF BRIDGE JOINTS** Added to the note to require inspection prior to work and specific language to protect membrane sealant expansion joints at the request of the Bridge Office.